

VERTICAL TURBINE DIESEL FIRE PUMP | 1000 GPM WITH 8×12 CAST IRON HEAD | SUBMITTAL

File No: F51.612 Date: JULY 15, 2013 Supersedes: F51.612 Date: AUGUST 15, 2005

Jop:	Representative:	_ Representative:					
	Order no.:	Date:					
Engineer:	Submitted by:	Date:					
Contractor:	Approved by:	Date:					
Model: 8×14M VTF Discharge hea	d: 8×12 A NOTES						
RPM: 1770 Water lube	Dimension base	ed on randolph gear drive. May vary when					
1000 GPM: T.D.H	driver adaptor is	s required.					
□ FM □ UL □ NFPA-20 only	• Dimensions are	in inches unless otherwise indicated.					
□ Approval □ Construction	installed and plu	mounting and cooling loop to be field umbed.					
Engine model:	- Engine oil & ant	i freeze/coolant may not be included.					
Ragd model:	- Gear shipped fil	lled with oil. Check level before installation					
Shaft model:	_ Refer dwg. no	for Engine dimensions.					
Controller model:	 Not to be used f 	for construction unless certified.					


PRESS	DISCHARGE FLANGE INCH (MM)							
RATE	DA	DC	DD	DF	DG	DK		
125 #		11.75 (299)		8.00 (203)	0.88 (22)	1.13 (29)		

FM Approved CULUS

NO OF STG'S	DISCHARGE SIZE	RATING	RAGD	AG*	В	с	Н*	۱*	L	AA
	INCH (mm)		НР	імсн (mm)						
2	8 (203)	125	60- 80-100	22.25 (565)	45.75 (1162)	1.25 (32)	8.50 (216)	17.00 (432)	_	_
3	8 (203)	125	80-100	22.25 (565)	55.64 (1413)	1.25 (32)	8.50 (216)	17.00 (432)	—	—
3	8 (203)	125	125- 150	26.69 (678)	55.64 (1413)	1.25 (32)	11.44 (291)	18.00 (457)	_	_

.....

* Dimension based on randolph gear drive. May vary when driver adaptor is required.



TORONTO

+1 416 755 2291

BUFFALO +1 716 693 8813

BIRMINGHAM

+44 (0) 8444 145 145

MANCHESTER

+44 (0) 8444 145 145

BANGALORE

+91 (0) 80 4906 3555

SHANGHAI

ARMSTRONG FLUID TECHNOLOGY ESTABLISHED 1934

ARMSTRONGFLUIDTECHNOLOGY.COM

+86 21 3756 6696